

**Format: 30 mm**

## Design requirements for your layout (UV-print):

- Graphic elements should have a minimum resolution of 300dpi
- PDF color space should be in CMYK (Coated FOGRA39)
- minimum line width is 0.3 mm
- Preferably created as vector graphics
- Sans serif fonts are preferred
- Fonts should be exported in paths/curves, otherwise include them in the email
- if possible, avoid using transparent gradients
- if white- or neonprint: Color in elements in white (CMYK 0,0,0,0)
- if you don't want a printed background, please keep it transparent (everything colored in white, will be printed in white)


## Send us the file with the following requirements:

- deliver print layout as .pdf document
- Send print layout without the red punch
- insert the print layout into the designated print image area
- Insert print layout for double-sided printing into the corresponding pages
- borderless printing: include a bleed of 1 mm on all sides to your layout
- Send your print layout to [print@nfc21.de](mailto:print@nfc21.de), quoting the order number and if you wish neon colors

**BB - 32 mm, bleed 2 mm**

**BE - 30 mm - final format**

**Perforation - 3 mm**



## Do you need any help?

NFC21 GmbH | [print@nfc21.de](mailto:print@nfc21.de) | +49 208 60 70 42 0

# Format: 30mm

Last updated: March 2024 - V1

